# Interactive Smoothing of Handwritten Text Images Using a Bilateral Filter


Oliver A. Nina, Bryan S. Morse

Brigham Young University

## The Problem

- An increasing number of people are using text images
- Volunteers read text images to index important information
- Many of the images are unreadable due to quality and age of the documents
- Artifacts in the images include background noise and undistinguishable ink strokes


## The Problem



#### The Solution

- We improve image visibility by,
- Using a bilateral filter to even out the noise in the background
- Accentuating weak stroke pixels to make them more visible (Laplacian)
- We can apply interactively the algorithm in desired regions
- We adjust the parameters of the algorithm to improve results

## The Solution



	Page 6
-	BURIALS in the Parish of Hope under Diamere in the County of Hereford in the year One thousand eight hundred and Eightly.
	Name. Abode. When baded. Age. 2, when the Decreased
pito.	Charlette Dale Leoninster. Feb 12 37 Whoyalt.
N.	William Stafford The Home april 12 94 Whoyatt.
	Edward Gongh. Woodinantin april 10. 76 looky att
land of the state	Thomas Smith. Hill Hole april 27 100 14 Challens
	Thomas Grafton Newston May 1st 67 Millioners
	James Gorduin Quinn The lite June 15th 64 M. and Les
	John Millich of The Figen Have gene 19th 10 2 wandrans
	Elizabeth Britha The Valletts June 29 60 W loyalt


Before

After

## Background


Bilateral Filter (Tomasi et al.1998)

Smooths regions while preserving edges



## Background - Bilateral Filter

- It uses 2 weighting functions
- G<sub>s</sub> = spatial normal distribution
- G<sub>r</sub> = range (color) normal distribution




## Background - Bilateral Filter

We combine the two weighing functions and we have:

$$I_p' = \sum G_s(|p-q|) G_r(|I_p-I_q) I_q / W_p$$

where

$$W_p = \sum G_s(|p-q|) G_r(|I_p-I_q)$$



## Background

#### **Laplacian Filter**

Calculates the 2nd derivative of the image (edge detection)

0	-1	0	-1	-1	-1
_1	4	<b>–1</b>	-1	8	-1
0	_1	0	-1	<b>–1</b>	-1


We combine it with the bilateral filter to augment soft strokes




## Our Algorithm

- We identify if the mouse is over an edge (ink stroke)
  - The Laplacian filter gives us zero crossings
- We apply the bilateral filter on mouse\_down and mouse\_move events
- If we are over an edge, we darken the stroke
- Otherwise, we make the background lighter


#### Results




Original Image



Result ( $G_r = 3$ ,  $G_s = 5$ )




Result ( $G_r = 3, G_s = 10$ )




Result ( $G_r = 3, G_s = 15$ )


### Results




Original Image



Result ( $G_r = 3$ ,  $G_s = 5$ )




Result ( $G_r = 3, G_s = 10$ )




Result ( $G_r = 3, G_s = 15$ )

## Results



Original Image



Result - Accentuated Strokes

#### Conclusion

- We applied the Bilateral filter and Laplacian to solve the problem of low quality text images
- Results are promising and indicate that;
- Bilateral filter is robust and smooths text images without losing important pixels
- Edge enhancement can make faint text more readable

#### Further Work

- Improve identifying the edges better, using a better edge detector.
- Automatically select the parameters to work with the bilateral and laplacian filters.
- Use the bilateral filter for text segmentation of old document images.

Questions?